

Cesoie SEIM:
la garanzia del monoblocco
significa prestazioni,
affidabilità, prezzo

SEIM cutters:
the guarantee of the one-block
cast means performance,
reliability, price

Corpo in monoblocco in acciaio fuso di alta qualità e rinforzato nei punti di maggior sollecitazione, completamente esente da parti in carpenteria. Coltelli in acciaio speciale temperato, appositamente studiati per il taglio sia di ferro di piccolo diametro che di grosso diametro (si possono utilizzare quattro spigoli di taglio). Gli ingranaggi sono in acciaio bonificato antiusura a lubrificazione perenne e le parti in movimento sono in acciaio temperato e rettificato.

The main body is one block in high-quality cast steel, reinforced in the points where the stress is higher, without any welded plate. The cutting blades, in special hardened steel, are designed to cut both small and big diameter iron (four cutting edges can be used). Gears are in wear-resistant steel, continuously lubricated, and the moving parts are in hardened and rectified steel.

Cesoie SEIM SEIM cutters

TR 26 - TR 30

TR 35 - TR 40



CARATTERISTICHE GENERALI

GENERAL FEATURES

Mod. TECMOR e SEIM	rpm.	n° barre n° rods	Diam. max. 650 N/mm ² FeB-44K	Diam. max. 850 N/mm ²	Mot. Kw	Dimensioni Size cm.	Peso Kg Weight
-----------------------	------	---------------------	--	-------------------------------------	------------	------------------------	-------------------

PIEGATRICI MONOFASE

MONO-PHASE BENDING MACHINES

PF 28	9	1	Ø 24	Ø 22	1,5	76 x 81 x 86 h	240
PG 26	10	1	Ø 22	Ø 20	0,75	86 x 76 x 88 h	230
PG 30	9	1	Ø 24	Ø 22	1,5	86 x 76 x 88 h	250

COMBIMATE MONOFASE

MONO-PHASE COMBINED MACHINES

PJT 32/25 (piegatura - bending)	10	1	Ø 24	Ø 22	1,5	80 x 88 x 86 h	290
PJT 32/25 (taglio - cutting)	10	1	Ø 20	Ø 18			
PFT 26/24 (piegatura - bending)	9	1	Ø 24	Ø 22	1,5	80 x 88 x 86 h	290
PFT 26/24 (taglio - cutting)	9	1	Ø 20	Ø 18			
PFT 32/26 (piegatura - bending)	9	1	Ø 26	Ø 24	1,5	80 x 88 x 86 h	320
PFT 32/26 (taglio - cutting)	9	1	Ø 22	Ø 20			

CESOIE TRIFASE

THREE-PHASE CUTTERS

C 24	110	1	Ø 20	Ø 18	1,1	65 x 40 x 61 h	120
		2	Ø 16	Ø 14			
		3	Ø 14	Ø 12			
C 30	110	1	Ø 26	Ø 22	2,2	45 x 85 x 70 h	250
		2	Ø 18	Ø 16			
		3	Ø 14	Ø 12			
C 35	100	1	Ø 30	Ø 26	2,2	53 x 92 x 72 h	330
		2	Ø 22	Ø 18			
		3	Ø 16	Ø 14			
C 40	60	1	Ø 34	Ø 30	3	60 x 100 x 85 h	390
		2	Ø 24	Ø 20			
		3	Ø 18	Ø 16			
C 45	50	1	Ø 38	Ø 34	3	110 x 65 x 100 h	580
		2	Ø 26	Ø 24			
		3	Ø 22	Ø 20			
C 55	50	1	Ø 46	Ø 40	4	130 x 69 x 110 h	670
		2	Ø 32	Ø 26			
		3	Ø 26	Ø 22			
TR 26	110	1	Ø 22	Ø 20	1,1	45 x 85 x 70 h	200
		2	Ø 16	Ø 14			
		3	Ø 14	Ø 12			
TR 30	110	1	Ø 26	Ø 22	2,2	45 x 85 x 70 h	220
		2	Ø 18	Ø 16			
		3	Ø 14	Ø 12			
TR 35	100	1	Ø 30	Ø 26	2,2	53 x 92 x 72 h	280
		2	Ø 22	Ø 18			
		3	Ø 16	Ø 14			
TR 40	70	1	Ø 34	Ø 30	3	53 x 100 x 100 h	360
		2	Ø 24	Ø 20			
		3	Ø 18	Ø 16			

CESOIE MONOFASE

MONO-PHASE CUTTERS

C 24	110	1	Ø 20	Ø 18	1,1	65 x 40 x 61 h	120
		2	Ø 16	Ø 14			
		3	Ø 14	Ø 12			
TR 26	110	1	Ø 22	Ø 20	1,1	45 x 85 x 70 h	200
		2	Ø 16	Ø 14			
		3	Ø 14	Ø 12			
TR 30	110	1	Ø 26	Ø 22	2,2	45 x 85 x 70 h	220
		2	Ø 18	Ø 16			
		3	Ø 14	Ø 12			
C 30	110	1	Ø 26	Ø 22	2,2	45 x 85 x 70 h	250
		2	Ø 18	Ø 16			
		3	Ø 14	Ø 12			