



MOTORE

Motore benzina

Marca e tipo	HONDA GX390
Cilindri e cilindrata	monocilindrico da 389 cm ³
Potenza lorda max	13 HP a 3600 g/1'
Regime di taratura	3500 g/1'
Avviamento elettrico	opzionale

Motore diesel

Marca e tipo	Yanmar L100AE
Cilindri e cilindrata	monocilindrico da 406 cm ³
Potenza lorda max	10 HP a 3600 g/1'
Regime di taratura	3500 g/1'
Avviamento elettrico	di serie



IMPIANTO IDRAULICO

Pompe: n. e tipo	3 ad ingranaggi da 4 cm ³
Portata	l/1' 15
Pressione	bar 150



CARRO

Tendicingolo a grasso, riduttori epicicloidali con motore orbitale.	
Larghezza cingolo	mm 180
Rulli di sostegno per lato	3 + slitta
Velocità di traslazione	Km/h 2,1 - 3,4
Allargamento idraulico opzionale	mm 750 / 1050



RIFORMIMENTI

Serbatoio olio	l 20
Serbatoio benzina	l 6,5
Serbatoio gasolio	l 5,5



PESO OPERATIVO

Peso operativo escluso operatore (carro fisso)	Kg 430
Peso operativo escluso operatore (carro allarg.)	Kg 490

PRESTAZIONI:

Portata (compreso kit)	kg 1100
------------------------------	---------

DOTAZIONI STANDARD:

- Seconda velocità di traslazione
- Attacchi idraulici rapidi per kit
- Pedana antiscivolo
- Scambiatore di calore
- Cingolo rinforzato

KIT DISPONIBILI:

- Pianale agricolo
- Cassone edile
- Cassone autocaricante
- Scarico alto edile e autocaricante
- Escavatore
- Spray
- Spaccalegna
- Verricello
- Betoniera
- Lama livellatrice



ENGINE

Gasoline engine

Brand and model	HONDA GX390
No. cylinders/cubic displacement	one-cylinder 389 cm ³
Max power	13 HP - 3600 g/1'
RPM	3500 g/1'
Electric starting	optional

Diesel engine

Brand and model	Yanmar L100AE
No. cylinders/cubic displacement	one-cylinder 406 cm ³
Max power	10 HP - 3600 g/1'
RPM	3500 g/1'
Electric starting	standard



HYDRAULIC SYSTEM

Pumps: No. and type	3 by gears - 4 cm ³
Capacity	l/1' 15
Pressure	bar 150



UNDERCARRIAGE

Track tension by grease, planetary gear-box with hydraulic orbital motor.	
Rubber track width	mm 180
No. rollers per side	3 + upper guide
Translation speed	Km/h 2,1 - 3,4
Optional hydraulic widening	mm 750 / 1050



PROVISIONS

Oil tank	l 20
Diesel tank	l 6,5
Gasoline tank	l 5,5



OPERATING WEIGHT

Operating weight without operator (fixed width undercarriage)		Kg 430
Operating weight without operator (variable width undercarriage)		Kg 490

PERFORMANCES:

Loading capacity (with kit)	kg 1100
-----------------------------------	---------

STANDARD EQUIPMENT:

- Second translation speed
- Hydraulic quick couplings for the kit
- Antisliding footboard
- Heat exchanger
- Reinforced tracks

AVAILABLE KITS:

- Farm bed
- Dumper bed
- Self-loading dumper bed
- Hi-tip
- Mini-excavator
- Spray
- Log splitter
- Winch
- Concrete mixer
- Levelling blade

OPTIONAL





HP1100

KIT CON SCARICO ALTO E CASSONE AUTOCARICANTE HI-TIP AND SELF-LOADING DUMPER BED KIT



Peso operativo escluso operatore (carro fisso)
Operating weight without operator
(fixed width undercarriage)

Kg 700

Peso operativo escluso operatore (carro allarg.)
Operating weight without operator
(variable width undercarriage)

Kg 790

Portata utile • Loading capacity

kg 400

Capacità cassone • Skip's capacity

m³ 0,21

**BREVETTATO
PATENTED**

